

AIR FILTRATION  
& AIR QUALITY



## HEPAGEL-78-ARM

Hepa Filters With Gel Gasket

### APPLICATIONS

- Used in systems made according to sealed with gel technique
- Clean rooms with LAF counters and operating rooms

### FILTER CODE STRUCTURE

Type	<b>HG</b>	HEPAGEL
Class EN 1822	<b>11</b>	%95 @0.3 μm
Frame	<b>A</b>	A: Aluminum
Media	<b>R</b>	R: Micro Glass Fibre S: Synthetic
Pleat Depth	<b>M</b>	S: 0.55-1 inch    K: 1-1.88 inch M: 1.9-2.28 inch
Surface Grid	<b>2</b>	0: Without Grid 1: Face Grid Air Outlet 2: Both Side with Grid
Gasket Type	<b>G</b>	Gel Type
Gasket Direction	<b>G</b>	C: Air Outlet G: Air Inlet
Size	24-24-3	

### TECHNICAL SPECIFICATIONS

Efficiency @0.3 μm	95 %	99 %	99,9 %	99.99 %	99.999 %	99.9999 %
Max. Temperature	176 °F (Optional 248 °F)					
Relative Humidity	100 %					
Rec. Final Pres. Drop	2.4 w.g.					
Filter Stage	III - IV					

For more information please click here.

