

AIR FILTRATION
& AIR QUALITY



HEPALAM-110-ARN

Laminar Flow Absolute Filters

APPLICATIONS

To be used for absolute air filtration in controlled contamination environments clean rooms, LAF benches and operating rooms

FILTER CODE STRUCTURE

Type	HL	HEPALAM
Class EN 1822	12	%99,9 @0.3 μm
Frame	A	A: Aluminum
Media	R	R: Micro Glass Fibre S: Synthetic Y: High Heat
Pleat Depth	N	S: 0.55-1inch K: 1-1.88 inch M: 1.9-2.28 inch N: 2.3-3 inch
Surface Grid	2	0: Without Grid 1: Face Grid Air Outlet 2: Both Side with Grid
Gasket Type	P	X: Without Gasket P: Polyurethane R: Rubber E: Epdm Y: High Heat
Gasket Direction	G	X: No C: Air Outlet G: Air Inlet W: Both Side
Size		25-25-5

TECHNICAL SPECIFICATIONS

Efficiency @0.3 μm	95%	99%	99,9%	99.99%	99.999%	99.9999%
Max. Temperature	176 °F (Optional 248 °F)					
Relative Humidity	100 %					
Rec. Final Pres. Drop	2.4 w.g.					
Filter Stage	III - IV					

For more information please click here.

