

AIR FILTRATION  
& AIR QUALITY



## HEPALAM-90-ARN

Laminar Flow Absolute Filters

### APPLICATIONS

To be used for absolute air filtration in controlled contamination environments clean rooms, LAF benches and operating rooms

### FILTER CODE STRUCTURE

Type	<b>HL</b>	HEPALAM-90
Class EN1822	<b>11</b>	%95 @0.3 µm
Frame	<b>A</b>	<b>A:</b> Aluminum <b>G:</b> Galvanized <b>T:</b> Stainless
Media	<b>R</b>	Micro Glass Fibre
Pleat Depth	<b>N</b>	<b>M:</b> 2.28 inch <b>L:</b> 3.94 inch <b>E:</b> 5.31 inch <b>D:</b> 5.90 inch <b>B:</b> 9.84 inch <b>K:</b> 1.89 inch <b>N:</b> 2.95 inch <b>S:</b> 0.98 inch
Surface Grid	<b>2</b>	<b>0:</b> Without Grid <b>1:</b> Face Grid Air Outlet <b>2:</b> Both Side with Grid
Gasket Type	<b>P</b>	<b>X:</b> Without Gasket <b>P:</b> Polyurethane <b>R:</b> Rubber <b>E:</b> Epdm <b>Y:</b> High Heat <b>V:</b> Triangle Gasket
Gasket Direction	<b>G</b>	<b>X:</b> No <b>C:</b> Air Outlet <b>G:</b> Air Inlet <b>W:</b> Both Side
Size		24-24-3

### TECHNICAL SPECIFICATIONS

Efficiency @0.3 µm	95%	99%	99,9%	99.99%	99.999%	99.9999%
Max. Temperature	176 °F [Optional 248 °F]					
Relative Humidity	100 %					
Rec. Final Pres. Drop	2.4 w.g.					
Filter Stage	III - IV					

For more information please click here.

