

AIR FILTRATION
& AIR QUALITY



MULTIAS 292-GRT8 & GRT5

Aluminium Separator Filters

APPLICATIONS

- High temperature resistant Aluminium separator
- In high-flow filter unit applications
- Low initial pressure drop
- Optional gasket, flange, protection grid wire

FILTER CODE STRUCTURE

Type	MA	MULTI-AS
Filter Class ASHRAE52.2	8	MERV 14
Frame	G	G: Galvanized A: Aluminum T: SS304 S: SS316
Media and Separator	R	R: Micro Glass Fibre Y: High Heat
Separator Depth	8	8: 0.32 inch 5: 0.2 inch 3: 0.12 inch
Flange Type	T	N: Without Flange T: 1 inch Single Flange D: 1 inch Double Flange V: 0.78 inch Single Flange W: 0.78 inch Double Flange B: Custom Size
Surface Grid	2	0: Without Grid 1: Face Grid Air Outlet 2: Both Side with Grid
Gasket Type	Y	X: Without Gasket P: Polyurethane R: Rubber E: Epdm Y: High Heat C: Cord Gasket
Gasket Direction	C	X: No C: Air Outlet G: Air Inlet W: Both Side
Size		24-24-12

TECHNICAL SPECIFICATIONS

ASHRAE52.2					
Class	MERV 9-10	MERV 11-12	MERV 13	MERV 14	MERV 15
Average Efficiency	50%≤E2	80%≤E2	50%≤E1	75%≤E1	85%≤E1
Max. Temperature	482 - 662°F				
Relative Humidity	100 %				
Rec. Final Pres. Drop	Initial Pressure Drop x2				
Filter Stage	II - III				

For more information please click here. 

