

PRE FILTERS

AIR FILTRATION
& AIR QUALITY



PREBAG-PR-600

Synthetic Rigid Pocket Filters

APPLICATIONS

- Conditioning, ventilation systems, power plants and turbo machines
- Used as pre-filter or second-stage filter
- Low start pressure drop
- High dust holding capacity
- Reduced operating costs
- Provides long service interval

FILTER CODE STRUCTURE

Type	MB	MULTIBAG-PR
Filter Class ASHRAE52.2	6	MERV11-12
Frame	V	G: Galvanized P: Plastic (Black - 1 inch) T: SS 304 S: SS 316 V: One Piece Plastic (1 inch)
Header Thickness	25	25: 1inch 20: 0.78 inch
Media	R	Rigid High Frequency
Pocket Number	08	8 Pockets
Gasket Type	X	X: Without Gasket P: Polyurethane R: Rubber E: EPDM
Gasket Direction	X	X: No C: Air Outlet G: Air Inlet W: Both Sides
Size		24-24-24

Fire Resistance Class K1/F1 According to DIN53438

TECHNICAL SPECIFICATIONS

ASHRAE52.2		
Class	MERV 9-10	MERV11-12
Average Efficiency	50% ≤ E2	80% ≤ E2
Max. Temperature	176°F	
Relative Humidity	100 %	
Rec. Final Pres. Drop	Initial Pressure Drop x2	
Filter Stage	II - III	

For more information please click here. 

